


AK

Connectors

End cap | transition from tubing to cable

Temperature:	-40°C ... +120°C ^ +150°C
--------------	---------------------------

Material:	TPE
-----------	-----



CHARACTERISTICS:

- Properties: easy mounting cap
- easy to plug on all protective conduits
- free of silicone-, cadmium-, halogen
- self-extinguishing



FLEXA No.	OD [mm]	Colour	cable-Clamp.range [mm]	D [mm]	Weight [kg/100]	PU [pcs.]
15030014207	10,0	black	1,0-8,0	29,0	0,160	50
15030014209	14,0	black	1,0-10,0	32,5	0,220	50
15030014211	17,0	black	4,0-12,0	35,5	0,340	50
15030014216	21,0	black	6,0-16,5	37,5	0,560	50
15030014221	27,0	black	6,0-23,0	40,2	0,800	25
15030014229	36,0	black	6,0-29,0	44,2	1,480	25
15030014236	45,0	black	10,0-37,0	45,5	1,480	25
15030014248	56,0	black	10,0-47,0	52,5	2,200	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.