


EE

**Connectors**

Terminal sleeve | ferrule for connectors EG, EW 45 and EW 90, as terminal sleeve for protective conduits

**Temperature:** -40°C ... +250°C

**Material:** brass

**APPLICATIONS:**

- Application: as terminal sleeve for protective conduits



FLEXA No.	OD [mm]	Conduitmaß [mm]	Ø l [mm]	Weight [kg/100]	PU [pcs.]
15031028009	5/16 inch	10,0-14,0	8,5	0,300	50
10601000011	3/8 inch	12,5-18,0	11,0	0,300	50
10601000016	1/2 inch	16,0-21,0	14,5	0,700	50
10601000021	3/4 inch	21,0-27,0	19,5	1,000	25
10601000029	1 inch	26,5-33,0	25,0	1,500	25
10601000036	1 1/4 inch	35,5-42,0	33,0	1,900	20
10601000048	2 inch	50,0-60,0	49,0	2,800	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.