

## EEM


## Connectors

Terminal sleeve | ferrule for connectors US and USW, as terminal sleeve for protective conduits

**Temperature:** -40°C ... +250°C

**Material:** brass

**for protective conduit:** FLEXAgraff-SI-ASF

**APPLICATIONS:**

- Application: for connectors US and USW / as terminal sleeve for protective conduits



FLEXA No.	OD [mm]	Conduitmaß [mm]	Ø l [mm]	Weight [kg/100]	PU [pcs.]
15031037009	14,0	10,0-14,0	9,0	0,160	50
15031037011	17,0	12,0-17,0	10,5	0,320	50
15031035016	21,0	16,0-21,0	14,5	0,520	50
10601000021	27,0	21,0-27,0	19,5	1,000	25
15031037029	36,0	27,0-36,0	26,5	1,640	25
15031037036	45,0	36,0-45,0	34,5	2,450	20
15031037048	56,0	47,0-56,0	45,5	3,800	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.