

## **EWM-M** | metric thread

## **Accessories**

Enlargement, extension of a metric thread into a larger

Temperature: -40°C ... +200°C


Material: nickel-plated brass

## CHARACTERISTICS:

- Properties: high stability







FLEXA No.	Outer thread	Inner thread	L1 [mm]	L [mm]	WS [mm]	Weight [kg 100]	PU [pcs.]
10360M12M16	M12x1, 5	M16x1, 5	5,0	16,0	18	1,070	100
10360M16M20	M16x1, 5	M20x1, 5	5,0	16,5	22	1,440	100
10360M20M25	M20x1, 5	M25x1, 5	6,0	18,5	27	2,050	100
10360M25M32	M25x1, 5	M32x1, 5	7,0	20,5	34	2,800	25
10360M32M40	M32x1, 5	M40x1, 5	8,0	23,5	42	5,360	25
10360M40M50	M40x1, 5	M50x1, 5	8,0	30,0	52	9,980	10
10360M50M63	M50x1, 5	M63x1, 5	9,0	32,5	65	15,200	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.