

## GMK-Duo-M

## Accessories

Counternut separable, especially for connector RQG-Duo-M with metric thread



**Temperature:** -40°C ... +110°C ^ +150°C

**Material:** PA 6 plastics

## CHARACTERISTICS:

- Properties: specifically for use in dividable cable protection systems
- simple assembly | disassembly



FLEXA No.	Colour	Thread type	C [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
10318000016	Black	M 16 x 1,5	10,0	26	0,160	10
10318000020	Black	M 20 x 1,5	10,0	26	0,180	10
10318000025	Black	M 25 x 1,5	10,0	28	0,200	10
10318000032	Black	M 32 x 1,5	10,0	36	0,400	5
10318000040	Black	M 40 x 1,5	12,0	46	0,900	5
10318000050	Black	M 50 x 1,5	12,0	56	1,200	5
10318000063	Black	M 63 x 1,5	12,0	71	1,850	5

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.