


**PBZ**

Connector with strain, connection and fixation of the PL guide chains



**Temperature:** -40°C ... +135°C

**Material:** PA6 GFK plastics



FLEXA No.	Article	for Type	Bi [mm]	EO [mm]	G [mm]	F [mm]	Tiewrap plates	PU [Set]
16153031000	Connector with strain relief PBZ	PL3	31,0	41,0	6,5	10,0	3	1
16154038000	Connector with strain relief	PL4	38,0	50,0	6,1	22,0	3	1
16154048000	Connector with strain relief	PL4	48,0	60,0	6,1	30,0	5	1
16154068000	Connector with strain relief	PL4	68,0	80,0	6,1	44,0	7	1
16155061000	Connector with strain relief	PL5	61,0	75,0	6,1	45,0	5	1
16155081000	Connector with strain relief	PL5	81,0	95,0	6,1	55,0	7	1
16155111000	Connector with strain relief	PL5	111,0	125,0	6,1	80,0	9	1

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.