


## REM-M | metric thread

## Accessories

Reducer, reduction of a metric thread to a smaller size



**Temperature:** -40°C ... +200°C

**Material:** nickel-plated brass

## CHARACTERISTICS:

- Properties: high stability



FLEXA No.	Outer thread	Inner thread	L1 [mm]	L [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
10350M16M12	M16x1,5	M12x1,5	5,0	8,0	17	0,750	100
10350M20M12	M20x1,5	M12x1,5	6,0	9,0	22,0	1,590	100
10350M20M16	M20x1,5	M16x1,5	6,0	9,0	22,0	0,950	100
10350M25M16	M25x1,5	M16x1,5	7,0	10,0	27,0	2,640	100
10350M25M20	M25x1,5	M20x1,5	7,0	10,0	27,0	1,740	100
10350M32M16	M32x1,5	M16x1,5	8,0	11,0	34,0	5,660	50
10350M32M20	M32x1,5	M20x1,5	8,0	11,0	34,0	4,400	50
10350M32M25	M32x1,5	M25x1,5	8,0	11,0	34,0	3,700	50
10350M40M20	M40x1,5	M20x1,5	8,0	12,0	43,0	10,000	25
10350M40M25	M40x1,5	M25x1,5	8,0	12,0	43,0	5,080	25
10350M40M32	M40x1,5	M32x1,5	8,0	12,0	43,0	6,360	25
10350M50M40	M50x1,5	M40x1,5	9,0	13,0	55,0	9,600	10
10350M63M32	M63x1,5	M32x1,5	10,0	14,0	65,0	27,850	10
10350M63M40	M63x1,5	M40x1,5	10,0	14,0	65,0	22,900	10
10350M63M50	M63x1,5	M50x1,5	10,0	14,0	65,0	17,900	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.