


REM-P | PG thread

Accessories

Reducer, reduction of a PG thread to a smaller size



Temperature: -40°C ... +200°C

Material: nickel-plated brass

CHARACTERISTICS:

- Properties: high stability



FLEXA No.	Outer thread	Inner thread	L1 [mm]	L [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
10350P09P07	PG9	PG7	6,0	8,5	18,0	0,460	100
10350P11P07	PG11	PG7	6,0	8,5	20,0	1,050	100
10350P11P09	PG11	PG9	6,0	8,5	20,0	0,650	100
10350P13P07	PG13, 5	PG7	6,5	9,5	24,0	1,500	100
10350P13P09	PG13, 5	PG7	6,5	9,5	24,0	1,090	100
10350P13P11	PG13, 5	PG11	6,5	9,5	24,0	0,490	100
10350P16P09	PG16	PG9	6,5	9,5	24,0	1,710	100
10350P16P11	PG16	PG11	6,5	9,5	24,0	1,010	100
10350P16P13	PG16	PG13, 5	6,5	9,5	24,0	0,610	100
10350P21P16	PG21	PG16	7,0	10,0	32,0	1,910	100
10350P29P16	PG29	PG16	8,0	11,5	41,0	6,500	50
10350P29P21	PG29	PG21	8,0	11,5	41,0	4,440	50
10350P36P21	PG36	PG21	9,0	12,5	50,0	11,920	25
10350P36P29	PG36	PG29	9,0	12,5	50,0	7,400	25

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.