

## RQB45-P | PG thread

## Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick-type, bend 45°, PG outer thread, integrated snap-in sleeve with sealing, high density


**Temperature:** -40°C ... +120°C

**Material:** PA plastics

**IP class [acc. to EN 60529]:** IP 68 | IP 69K

**CHARACTERISTICS:**

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen

**APPLICATIONS:**

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations



FLEXA No.	Colour	OD [mm]	Thread type	Ø I [mm]	Ø B [mm]	C [mm]	E [mm]	F [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020089209	Black	13,0	PG9	8,5	20,0	12,0	41,0	48,0	21	0,800	50
15020089211	Black	15,8	PG11	10,0	20,0	12,0	43,0	51,0	24	1,200	50
15020089216	Black	21,2	PG16	14,5	29,5	13,0	54,0	56,0	26	2,000	50
15020089221	Black	28,5	PG21	20,0	37,0	14,0	63,0	69,0	36	2,900	25
15020089229	Black	34,5	PG29	29,0	44,0	14,0	70,5	73,5	45	4,100	10
15020089236	Black	42,5	PG36	36,0	52,0	17,0	81,0	82,5	58	6,000	10
15020089248	Black	54,5	PG48	45,0	64,0	17,0	95,0	97,0	69	8,500	5

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.