

RQB90-P | PG thread

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick-type, bend 90°, PG outer thread, integrated snap-in sleeve with sealing, high density


Temperature: -40°C ... +120°C

Material: PA plastics

IP class [acc. to EN 60529]: IP 68 | IP 69K

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen



APPLICATIONS:

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations



FLEXA No.	Colour	OD [mm]	Thread type	Ø I [mm]	Ø B [mm]	C [mm]	E [mm]	F [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020090207	Black	10,0	PG7	6,5	17,0	10,0	57,0	39,0	18	0,800	50
15020090209	Black	13,0	PG9	8,5	20,0	12,0	59,0	40,5	21	1,000	50
15020090211	Black	15,8	PG11	10,0	23,0	12,0	62,0	45,0	24	1,300	50
15020090213	Black	18,5	PG13,5	12,5	25,0	12,0	65,0	47,0	27	1,700	50
15020090216	Black	21,2	PG16	14,5	29,5	13,0	73,0	48,0	26	2,100	50
15020090221	Black	28,5	PG21	20,0	37,0	14,0	85,0	64,0	36	3,320	25
15020090229	Black	34,5	PG29	30,0	44,0	14,0	100,5	74,0	45	5,200	10
15020090236	Black	42,5	PG36	36,0	52,0	17,0	108,00	82,5	58	8,300	10
15020090248	Black	54,5	PG48	45,5	64,0	15,5	124,5	97,0	70	11,600	5

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.