

## RQE

### Connectors FLEXAquick for ROHRflex corrugated plastic tubings


End cap | transition from tubing to cable, rational tubing end, assembled by just putting on

**Temperature:** -40°C ... +120°C

**Material:** TPE plastics

#### CHARACTERISTICS:

- Characteristics: Resistance to methanol, silicone grease
- hydrogen
- seawater
- resistant to ozone



#### APPLICATIONS:

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations



FLEXA No.	Colour	OD [mm]	Clamp.range [mm]	D [mm]	Weight [kg/m]	PU [pcs.]
15030012207	black	10,0	1,0-8,0	29,0	0,120	50
15030012209	black	13,0	1,0-10,0	29,0	0,220	50
15030012211	black	15,8	4,0-12,0	36,0	0,320	50
15030012213	black	18,5	4,0-13,0	37,5	0,520	50
15030012216	black	21,2	6,0-16,5	37,0	0,560	50
15030012221	black	28,5	6,0-23,0	40,0	0,650	25
15030012229	black	34,5	6,0-29,0	44,0	0,960	25
15030012236	black	42,5	10,0-37,0	46,0	1,480	25
15030012248	black	54,5	10,0-47,0	53,0	2,100	10
15030012007	grey	10,0	1,0-8,0	29,0	0,120	50
15030012009	grey	13,0	1,0-10,0	29,0	0,220	50
15030012011	grey	15,8	4,0-12,0	36,0	0,320	50
15030012013	grey	18,5	4,0-13,0	37,5	0,520	50
15030012016	grey	21,2	6,0-16,5	37,0	0,560	50
15030012021	grey	28,5	6,0-23,0	40,0	0,800	25
15030012029	grey	34,5	6,0-29,0	44,0	0,960	25
15030012036	grey	42,5	10,0-37,0	46,0	1,480	25
15030012048	grey	54,5	10,0-47,0	53,0	2,100	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.