

RQG3-M | metric thread

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick-type, straight, metric inner thread, integrated snap-in sleeve, conically sealed


Temperature: -40°C ... +120°C

Material: PA plastics

IP class [acc. to EN 60529]: IP 66

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen



APPLICATIONS:

- Application: machine and plant constructions / automotive / electrical installations



FLEXA No.	OD [mm]	Colour	Thread type	$\varnothing l$ [mm]	$\varnothing B$ [mm]	$\varnothing B 1$ [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020079215	13,0	Black	M12 x 1,5	10,0	20,0	23,0	9,5	34,5	18	0,580	50
15020079214	13,0	Black	M16 x 1,5	10,0	20,0	21,0	9,5	36,5	18	0,660	50
15020079216	15,8	Black	M16 x 1,5	12,5	23,0	21,0	9,5	39,0	21	0,780	50
15020079220	21,2	Black	M20 x 1,5	16,5	29,5	24,0	12,5	49,0	27	1,280	50
15020079225	28,5	Black	M25 x 1,5	17,0	37,0	30,0	13,5	54,0	34	2,120	25
15020079232	34,5	Black	M32 x 1,5	24,0	44,0	35,0	15,0	55,5	40	2,680	10
15020079240	42,5	Black	M40 x 1,5	33,0	52,0	44,5	20,0	63,0	50	3,400	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.