

## RQG3-U | UNEF thread

## Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick-type, straight, UNEF inner thread, integrated snap-in sleeve, conically sealed


Temperature: -40°C ... +120°C

Material: PA plastics

IP class [acc. to EN 60529]: IP 66

## CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen



## APPLICATIONS:

- Application: machine and plant constructions / automotive / electrical installations



FLEXA No.	Colour	OD [mm]	Thread type	$\varnothing l$ [mm]	$\varnothing B$ [mm]	$\varnothing B 1$ [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020054202	Black	13,0	UNEF 1/2" -28	10,0	17,0	17,0	8,0	36,6	18	0,560	50
15020054203	Black	13,0	UNEF 5/8" -24	10,0	20,6	20,6	8,0	36,6	18	0,640	50
15020054205	Black	13,0	UNEF 3/4" -20	10,0	23,0	23,0	9,5	38,5	18	0,840	50
15020054204	Black	15,8	UNEF 5/8" -24	12,5	23,6	23,6	9,5	40,0	21	0,810	50
15020054232	Black	15,8	UNEF 11/16" -24	12,5	23,6	23,6	9,5	46,0	21	1,000	50
15020054206	Black	15,8	UNEF 3/4" -20	12,5	23,6	23,6	9,5	41,7	21	0,940	50
15020054225	Black	15,8	UNEF 15/16" -20	12,5	30,0	30,0	9,5	45,5	21	1,340	50
15020054210	Black	15,8	UNEF 1" -20	12,5	30,0	30,0	9,5	45,5	21	1,340	50
15020054239	Black	21,2	UNEF 9/16" -24	12,5	29,5	20,0	8,0	44,6	27	1,100	50
15020054207	Black	21,2	UNEF 5/8" -24	12,5	30,1	30,1	9,5	45,0	27	1,100	50
15020054227	Black	21,2	UNEF 3/4" -20	12,5	30,0	30,0	9,5	51,5	27	1,350	50
15020054208	Black	21,2	UNEF 7/8" -20	17,0	29,5	29,5	9,5	50,5	27	1,480	50
15020054209	Black	21,2	UNEF 15/16" -20	17,0	30,1	30,1	9,5	50,3	27	1,820	50
15020054211	Black	21,2	UNEF 1" -20	17,0	30,1	30,1	9,5	50,3	27	1,660	50
15020054226	Black	21,2	UNEF 1 1/8" -18	17,0	33,5	33,5	9,5	52,5	27	1,740	50
15020054212	Black	21,2	UNEF 1 3/16" -18	17,0	34,6	34,6	9,5	52,3	27	1,700	50
15020054222	Black	21,2	UNEF 1 3/8" -18	17,0	41,0	41,0	9,5	52,5	27	2,300	50
15020054215	Black	21,2	UNEF 1 7/16" -18	17,0	41,0	41,0	9,5	52,5	27	2,100	50
15020054219	Black	21,2	UNEF 1 3/4" -18	17,0	49,0	49,0	9,5	52,5	27	2,480	50
15020054223	Black	28,5	UNEF 15/16" -20	17,0	37,0	37,0	9,5	52,5	34	2,320	25
15020054214	Black	28,5	UNEF 1" -20	23,5	37,0	37,0	9,5	54,0	34	2,080	25
15020054213	Black	28,5	UNEF 1 3/16" -18	23,5	37,0	37,0	9,5	52,5	34	2,160	25



FLEXA No.	Colour	OD [mm]	Thread type	Ø I [mm]	Ø B [mm]	Ø B1 [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020054216	Black	28,5	UNEF 1 3/8" -18	23,5	41,0	41,0	9,5	54,0	34	2,680	25
15020054217	Black	28,5	UNEF 1 7/16" -18	23,5	41,0	41,0	9,5	54,0	34	2,600	25
15020054236	Black	28,5	UNEF 3/4" -18	23,5	49,0	49,0	9,5	54,0	34	2,300	25
15020054233	Black	34,5	UNEF 1" -20	23,5	43,5	43,5	9,5	56,0	40	2,300	10
15020054234	Black	34,5	UNEF 1 3/16" -18	17,0	43,5	43,5	9,5	40,0	40	2,300	10
15020054224	Black	34,5	UNEF 1 3/8" -18	23,5	52,0	52,0	9,5	56,0	40	3,300	10
15020054218	Black	34,5	UNEF 1 7/16" -18	30,5	44,0	44,0	9,5	55,0	40	2,800	10
15020054220	Black	34,5	UNEF 1 3/4" -18	30,5	49,0	49,0	9,5	56,0	40	3,100	10
15020054221	Black	34,5	UNEF 2" -18	30,5	55,0	55,0	9,5	56,0	40	3,250	10
15020054231	Black	42,5	UNEF 1 3/16" -18	23,0	52,0	52,0	9,5	56,0	48	3,100	10
15020054228	Black	42,5	UNEF 1 7/16" -18	30,5	52,0	52,0	9,5	57,0	48	3,100	10
15020054229	Black	42,5	UNEF 1 3/4" -18	30,5	52,0	52,0	9,5	58,5	48	3,100	10
15020054238	Black	42,5	UNEF 2" -18	30,5	54,5	54,5	9,5	60,0	48	4,180	10
15020054237	Black	42,5	UNEF 2 1/4" -16	30,5	66,5	66,5	18,0	70,0	48	4,500	10
15020054235	Black	54,5	UNEF 2 1/4" -16	49,5	66,5	66,5	18,0	70,0	60	5,000	10



Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.