


RQ GK2-P | PG thread

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick-type, straight, PG nickel-plated brass inner thread, integrated snap-in sleeve with sealing, high density, EN 45545-2 (HL3)



Temperature:	-40°C ... +120°C
Material:	PA plastics nickel-plated brass 58
IP class [acc. to EN 60529]:	IP 68 IP 69K

APPLICATIONS:

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen
- fit for high mechanical stress
- impact-resistant
- high torque of thread connection




ELECTRO-PRODUCTS CORP

FLEXA No.	OD [mm]	Colour	Thread type	ø I [mm]	ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020075207	10,0	Black	PG7	7,0	20,0	8,0	38,0	18	0,900	50
15020075209	13,0	Black	PG9	8,5	24,0	9,5	41,0	22	1,500	50
15020075211	15,8	Black	PG11	11,0	27,0	9,0	43,0	25	2,300	50
15020075213	18,5	Black	PG13,5	12,5	29,0	9,5	45,0	26	2,640	50
15020075216	21,2	Black	PG16	15,0	33,0	13,0	49,0	31	3,160	25
15020075221	28,5	Black	PG21	18,5	41,0	13,0	48,0	39	4,400	25
15020075229	34,5	Black	PG29	27,5	48,0	14,0	56,5	46	6,840	25
15020075236	42,5	Black	PG36	36,0	59,0	15,5	85,0	55	10,300	10
15020075248	54,5	Black	PG48	38,5	60,0	16,0	98,0	65	17,300	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.