


RQGKZE-M | metric thread

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick-type, straight, metric nickel-plated brass outer thread, integrated snap-in sleeve with sealing, strain relief and shielding, high density, EN 45545-2 (HL3)



Temperature:	-40°C ... +120°C
Material:	PA plastics nickel-plated brass 58
IP class [acc. to EN 60529]:	IP 68 IP 69K

APPLICATIONS:

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations / EMC applications

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen
- fit for high mechanical stress
- impact-resistant
- high torque of thread connection
- optimal held and sealing of cables at the same time



To ensure a high protection system between cable gland insert and screw connector housing it is necessary to use a sealing compound. (please see our assembly instructions)

KIBIS

ELECTRO-PRODUCTS CORP.

FLEXA No.	OD [mm]	Colour	Thread type	Clamp.range [mm]	Ø1 [mm]	ØB [mm]	C [mm]	D [mm]	WS1 [mm]	WS2 [mm]	Weight [kg/100]	PU [pcs.]
15111013216	13,0	Black	M16 x 1,5	5,0-8,5	8,5	24,0	5,0	55,0	22	17	3,440	50
15111015220	15,8	Black	M20 x 1,5	7,5-10,0	11,0	27,0	6,0	61,0	25	22	3,500	50
15111021220	21,2	Black	M20 x 1,5	10,0-12,5	12,5	33,0	6,0	64,0	30	22	6,470	25
15111021225	21,2	Black	M25 x 1,5	9,0-16,0	15,5	33,0	7,0	69,0	31	27	6,780	25
15111028225	28,5	Black	M25 x 1,5	11,0-16,0	16,0	42,8	7,0	71,0	41	27	6,720	25
15111034232	34,5	Black	M32 x 1,5	14,5-20,5	21,0	48,0	8,0	79,0	46	34	11,200	25
15111042240	42,5	Black	M40 x 1,5	21,0-26,0	27,0	57,3	8,0	106,0	55	43	18,960	10
15111054250	54,5	Black	M50 x 1,5	25,0-35,0	35,5	68,0	9,0	122,0	65	55	31,470	10
15111054263	54,5	Black	M63 x 1,5	32,0-41,5	41,5	73,0	10,0	124,0	65	65	39,460	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.