


RQGKZP-M

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick-type, straight, metric nickel-plated brass outer thread, integrated snap-in sleeve with sealing, strain relief, high density, EN 45545-2 and EN 45545-3 (HL3)



Temperature: -40°C ... +120°C

Material: PA plastics | nickel-plated brass 58

IP class [acc. to EN 60529]: IP 68 | IP 69K

APPLICATIONS:

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen
- fit for high mechanical stress
- impact-resistant
- high torque of thread connection
- optimal held and sealing of cables at the same time
- one-piece terminal block for isolation gentle fixation



To ensure a high protection system between cable gland insert and screw connector housing it is necessary to use a sealing compound. (please see our assembly instructions)

FLEXA No.	OD [mm]	Colour	Thread type	Clamp.range [mm]	Ø 1 [mm]	Ø B [mm]	C [mm]	D [mm]	WS1 [mm]	WS2 [mm]	Weight [kg/100]	PU [pcs.]
15112013216	13,0	Black	M16 x 1,5		8,5	24,0	6,0	56,5	22	18	2,600	50
15112113216	13,0	Black	M16 x 1,5	4,0-6,0	8,5	24,0	6,0	56,5	22	18	2,600	50
15112213216	13,0	Black	M16 x 1,5	5,0-8,0	8,5	24,0	6,0	56,5	22	18	2,600	50
15112313216	13,0	Black	M16 x 1,5	6,5-9,5	8,5	24,0	6,0	56,5	22	18	2,600	50
15112513216	13,0	Black	M16 x 1,5		8,5	24,0	15,0	65,5	22	18	2,750	50
15112613216	13,0	Black	M16 x 1,5	4,0-6,0	8,5	24,0	15,0	65,5	22	18	2,750	50
15112713216	13,0	Black	M16 x 1,5	5,0-8,0	8,5	24,0	15,0	65,5	22	18	2,750	50
15112813216	13,0	Black	M16 x 1,5	6,5-9,5	8,5	24,0	15,0	65,5	22	18	2,750	50
15112015220	15,8	Black	M20 x 1,5		11,0	27,0	6,5	57,0	25	22	3,500	50
15112115220	15,8	Black	M20 x 1,5	4,0-6,0	11,0	27,0	6,5	57,0	25	22	3,500	50
15112215220	15,8	Black	M20 x 1,5	6,5-9,5	11,0	27,0	6,5	57,0	25	22	3,500	50
15112315220	15,8	Black	M20 x 1,5	7,0-10,0	11,0	27,0	6,5	57,0	25	22	3,500	50
15112515220	15,8	Black	M20 x 1,5		11,0	27,0	6,5	57,0	25	22	3,650	50
15112615220	15,8	Black	M20 x 1,5	4,0-6,0	11,0	27,0	15,0	65,5	25	22	3,650	50
15112715220	15,8	Black	M20 x 1,5	6,5-9,5	11,0	27,0	15,0	65,5	25	22	3,650	50
15112815220	15,8	Black	M20 x 1,5	7,0-10,5	11,0	27,0	15,0	65,5	25	22	3,650	50
15112021220	21,2	Black	M20 x 1,5		11,0	27,0	6,5	57,0	25	22	3,500	50
15112121220	21,2	Black	M20 x 1,5	6,5-9,5	11,0	27,0	6,5	57,0	25	22	3,500	50
15112221220	21,2	Black	M20 x 1,5	7,0-10,5	11,0	27,0	6,5	57,0	25	22	3,500	50
15112321220	21,2	Black	M20 x 1,5	9,0-13,0	11,0	27,0	6,5	57,0	25	22	3,500	50
15112521220	21,2	Black	M20 x 1,5		11,0	27,0	15,0	65,5	25	22	3,650	50
15112621220	21,2	Black	M20 x 1,5	6,5-9,5	11,0	27,0	15,0	65,5	25	22	3,650	50



FLEXA No.	OD [mm]	Colour	Thread type	Clamp.range [mm]	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS1 [mm]	WS2 [mm]	Weight [kg/100]	PU [pcs.]
15112721220	21,2	Black	M20 x 1,5	7,0-10,5	11,0	27,0	15,0	65,5	25	22	3,650	50
15112821220	21,2	Black	M20 x 1,5	9,0-13,0	11,0	27,0	15,0	65,5	25	22	3,650	50
15112021225	21,2	Black	M25 x 1,5		16,0	33,0	7,5	65,0	28	28	5,600	25
15112121225	21,2	Black	M25 x 1,5	9,0-13,0	16,0	33,0	7,5	65,0	28	28	5,600	25
15112221225	21,2	Black	M25 x 1,5	11,5-15,5	16,0	33,0	7,5	65,0	28	28	5,600	25
15112521225	21,2	Black	M25 x 1,5		16,0	33,0	15,0	72,5	28	28	5,780	25
15112621225	21,2	Black	M25 x 1,5	9,0-13,0	16,0	33,0	15,0	72,5	28	28	5,780	25
15112721225	21,2	Black	M25 x 1,5	11,5-15,5	16,0	33,0	15,0	72,5	28	28	5,780	25
15112028225	28,5	Black	M25 x 1,5		16,0	33,0	7,5	65,0	28	28	5,600	25
15112128225	28,5	Black	M25 x 1,5	9,0-13,0	16,0	33,0	7,5	65,0	28	28	5,600	25
15112228225	28,5	Black	M25 x 1,5	11,5-15,5	16,0	33,0	7,5	65,0	28	28	5,600	25
15112528225	28,5	Black	M25 x 1,5		16,0	33,0	15,0	72,5	28	28	5,780	25
15112628225	28,5	Black	M25 x 1,5	9,0-13,0	16,0	33,0	15,0	72,5	28	28	5,780	25
15112728225	28,5	Black	M25 x 1,5	11,5-15,5	16,0	33,0	15,0	72,5	28	28	5,780	25
15112028232	28,5	Black	M32 x 1,5		20,0	41,0	8,0	71,0	31	35	8,500	25
15112128232	28,5	Black	M32 x 1,5	14,0-18,0	20,0	41,0	8,0	71,0	31	35	8,500	25
15112228232	28,5	Black	M32 x 1,5	17,0-18,6	20,0	41,0	8,0	71,0	31	35	8,500	25
15112528232	28,5	Black	M32 x 1,5		20,0	41,0	15,0	78,0	31	35	8,650	25
15112628232	28,5	Black	M32 x 1,5	14,0-18,0	20,0	41,0	15,0	78,0	31	35	8,650	25
15112728232	28,5	Black	M32 x 1,5	17,0-18,6	20,0	41,0	15,0	78,0	31	35	8,650	25
15112034240	34,5	Black	M40 x 1,5		27,5	48,0	8,0	75,0	42	43	13,400	25
15112134240	34,5	Black	M40 x 1,5	20,0-25,0	27,5	48,0	8,0	75,0	42	43	13,400	25
15112234240	34,5	Black	M40 x 1,5	24,0-28,5	27,5	48,0	8,0	75,0	42	43	13,400	25
15112534240	34,5	Black	M40 x 1,5		27,5	48,0	15,0	82,0	42	43	13,550	25
15112634240	34,5	Black	M40 x 1,5	20,0-25,0	27,5	48,0	15,0	82,0	42	43	13,550	25
15112734240	34,5	Black	M40 x 1,5	24,0-28,0	27,5	48,0	15,0	82,0	42	43	13,550	25
15112042250	42,5	Black	M50 x 1,5		36,0	60,0	10,0	82,0	50	57	17,800	10
15112142250	42,5	Black	M50 x 1,5	27,0-32,0	36,0	60,0	10,0	82,0	50	57	17,800	10
15112242250	42,5	Black	M50 x 1,5	32,0-36,0	36,0	60,0	10,0	82,0	50	57	17,800	10
15112542250	42,5	Black	M50 x 1,5		36,0	60,0	15,0	87,0	50	57	18,000	10
15112642250	42,5	Black	M50 x 1,5	27,0-32,0	36,0	60,0	15,0	87,0	50	57	18,000	10
15112742250	42,5	Black	M50 x 1,5	32,0-36,0	36,0	60,0	15,0	87,0	50	57	18,000	10
15112054250	54,5	Black	M50 x 1,5		36,0	60,0	15,0	82,0	50	57	17,800	10
15112154250	54,5	Black	M50 x 1,5	32,0-36,0	36,0	60,0	10,0	82,0	50	57	17,800	10
15112254250	54,5	Black	M50 x 1,5	36,0-40,0	36,0	60,0	10,0	82,0	50	57	17,800	10
15112554250	54,5	Black	M50 x 1,5		36,0	60,0	15,0	87,0	50	57	18,000	10
15112654250	54,5	Black	M50 x 1,5	32,0-36,0	36,0	60,0	15,0	87,0	50	57	18,000	10
15112754250	54,5	Black	M50 x 1,5	36,0-40,0	36,0	60,0	15,0	87,0	50	57	18,000	10
15112054263	54,5	Black	M63 x 1,5		47,5	72,0	10,0	90,0	61	68	28,400	10
15112154263	54,5	Black	M63 x 1,5	36,0-40,0	47,5	72,0	10,0	90,0	61	68	28,400	10
15112254263	54,5	Black	M63 x 1,5	40,0-44,0	47,5	72,0	10,0	90,0	61	68	28,400	10
15112554263	54,5	Black	M63 x 1,5		47,5	72,0	15,0	95,0	61	68	28,650	10
15112654263	54,5	Black	M63 x 1,5	36,0-40,0	47,5	72,0	15,0	95,0	61	68	28,650	10
15112754263	54,5	Black	M63 x 1,5	40,0-44,0	47,5	72,0	15,0	95,0	61	68	28,650	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.