

RQGZ1-P | PG thread

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic connector, quick-type, straight, PG outer thread, integrated snap-in sleeve, strain relief, conically sealed


Temperature: -40°C ... +120°C

Material: PA plastics

IP class [acc. to EN 60529]: IP 66


CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen
- optimal held and sealing of cables at the same time



APPLICATIONS:

- Application: machine and plant constructions / automotive / automation / electrical installations



| FLEXA No. | OD [mm] | Colour | Thread type | Clamp.range [mm] | Ø 1 [mm] | Ø B [mm] | C [mm] | D [mm] | WS1 [mm] | WS2 [mm] | Weight [kg/100] | PU [pcs.] |
|-------------|---------|--------|-------------|------------------|----------|----------|--------|--------|----------|----------|-----------------|-----------|
| 15020060207 | 10,0 | Black | PG7 | 3,0-6,5 | 7,0 | 17,0 | 8,0 | 51,0 | 16 | 15 | 0,750 | 20 |
| 15020060209 | 13,0 | Black | PG9 | 4,0-8,0 | 8,0 | 20,0 | 8,0 | 53,0 | 18 | 19 | 1,050 | 20 |
| 15020060211 | 15,8 | Black | PG11 | 5,0-10,0 | 10,0 | 23,0 | 8,0 | 59,0 | 21 | 22 | 1,450 | 20 |
| 15020060213 | 15,8 | Black | PG13,5 | 6,0-11,0 | 12,0 | 27,0 | 9,0 | 59,0 | 21 | 24 | 1,600 | 20 |
| 15020060215 | 21,2 | Black | PG13,5 | 6,0-12,0 | 12,0 | 29,5 | 9,0 | 70,0 | 27 | 24 | 2,300 | 10 |
| 15020060216 | 21,2 | Black | PG16 | 10,0-14,0 | 14,0 | 29,5 | 10,0 | 72,0 | 27 | 27 | 2,400 | 10 |
| 15020060221 | 28,5 | Black | PG21 | 13,0-18,0 | 18,0 | 37,0 | 11,0 | 82,0 | 34 | 33 | 3,400 | 10 |
| 15020060229 | 34,5 | Black | PG29 | 18,0-25,0 | 25,0 | 44,0 | 11,0 | 85,0 | 40 | 42 | 5,000 | 10 |
| 15020060236 | 42,5 | Black | PG36 | 22,0-32,0 | 32,0 | 52,0 | 13,0 | 106,0 | 49 | 53 | 8,500 | 10 |
| 15020060248 | 54,5 | Black | PG48 | 34,0-44,0 | 44,0 | 64,0 | 14,0 | 112,0 | 60 | 65 | 11,800 | 10 |

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.