

RQHD

Tubing clamp systems for light, medium and heavy duty applications

Cover RQHD for tubing clamp RQH, V2 (UL 94)



Temperature: -40°C ... +120°C

Material: PA plastics

APPLICATIONS:

- Application: for light applications / machine and plant constructions / insulated electrical installations for application rules machine and plant constructions acc. to DIN EN 60204



FLEXA No.	Colour	OD [mm]	Weight [kg/100]	PU [pcs.]
15030026207	Black	10,0	0,060	50
15030026209	Black	13,0	0,072	50
15030026211	Black	15,8	0,080	50
15030026213	Black	18,5	0,100	50
15030026216	Black	21,2	0,120	50
15030026221	Black	28,5	0,160	25
15030026229	Black	34,5	0,200	25
15030026236	Black	42,5	0,360	25
15030026248	Black	54,5	0,500	10
15030026007	Grey	10,0	0,060	50
15030026009	Grey	13,0	0,072	50
15030026011	Grey	15,8	0,080	50
15030026013	Grey	18,5	0,100	50
15030026016	Grey	21,2	0,120	50
15030026021	Grey	28,5	0,160	25
15030026029	Grey	34,5	0,200	25
15030026036	Grey	42,5	0,360	25
15030026048	Grey	54,5	0,500	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.