

RQHG

Tubing clamp systems for light, medium and heavy duty applications

Tubing clamp with cover for light applications with through hole for fastening by screws, ribbed fixing for strain relief, assembly of varying sizes joined feasible, applicable in combination with C-profile bars, V2 (UL 94)



Temperature: -40°C ... +120°C

Material: PA plastics

CHARACTERISTICS:

- Properties: ribbed fixing
- for strain relief
- assembly of varying sizes joined in line
- using in combination with C-profile bar

APPLICATIONS:

- Application: for light applications / machine and plant constructions / insulated electrical installations for application rules machine and plant constructions acc. to DIN EN 60204



FLEXA No.	Colour	OD [mm]	A [mm]	B [mm]	D [mm]	E [mm]	Ø I [mm]	Weight [kg/100]	PU [pcs.]
15030028207	Black	10,0	19,5	19,0	13,0	15,0	5,5	0,400	50
15030028209	Black	13,0	19,5	22,6	14,5	15,0	5,5	0,420	50
15030028211	Black	15,8	21,5	25,4	16,1	15,0	5,5	0,460	50
15030028213	Black	18,5	24,5	29,0	18,0	15,0	5,5	0,580	50
15030028216	Black	21,2	26,5	33,0	21,0	15,0	6,5	0,660	50
15030028221	Black	28,5	34,7	39,4	22,7	15,0	6,5	0,920	25
15030028229	Black	34,5	40,0	44,4	26,0	15,0	6,5	1,080	25
15030028236	Black	42,5	54,0	55,5	30,0	20,0	6,5	2,364	25
15030028248	Black	54,5	67,0	69,0	39,0	17,0	6,5	3,200	10
15030028007	Grey	10,0	19,5	19,0	13,0	15,0	5,5	0,400	50
15030028009	Grey	13,0	19,5	22,6	14,5	15,0	5,5	0,420	50
15030028011	Grey	15,8	21,5	25,4	16,1	15,0	5,5	0,460	50
15030028013	Grey	18,5	24,5	29,0	18,0	15,0	5,5	0,580	50
15030028016	Grey	21,2	26,5	33,0	21,0	15,0	6,5	0,660	50
15030028021	Grey	28,5	34,7	39,4	22,7	15,0	6,5	0,920	25
15030028029	Grey	34,5	40,0	44,4	26,0	15,0	6,5	1,080	25
15030028036	Grey	42,5	54,0	55,5	30,0	20,0	6,5	2,364	25
15030028048	Grey	54,5	67,0	69,0	39,0	17,0	6,5	3,200	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.