

## RQK-PA

**Connectors FLEXAquick for ROHRflex corrugated plastic tubings**

Plastic connector, quick-type, coupler for rational tubing assembly by just putting on, high-density, EN 45545-2 (HL2)



**Temperature:** -40°C ... +120°C

**Material:** PA plastics

**IP class [acc. to EN 60529]:** IP 68 | IP 69K

**APPLICATIONS:**

- Application: for static and dynamic applications indoor and outdoor of railway cars / heavy machine and plant constructions / insulated electrical installations for application rules machine and plant constructions acc. to DIN EN 60204



| FLEXA No.   | Colour | OD [mm]                 | Ø B1 [mm] | Ø B2 [mm] | Ø I [mm] | D [mm] | Weight [kg/100] | PU [pcs.] |
|-------------|--------|-------------------------|-----------|-----------|----------|--------|-----------------|-----------|
| 15602021221 | Black  | OD1 - 21,2 / OD2 - 21,2 | 29,5      | 29,5      | 17,0     | 80,0   | 2,600           | 10        |
| 15602028228 | Black  | OD1 - 28,5 / OD2 - 28,5 | 37,0      | 37,0      | 23,5     | 86,5   | 3,500           | 10        |
| 15602034234 | Black  | OD1 - 34,5 / OD2 - 34,5 | 44,0      | 44,0      | 30,0     | 91,5   | 4,700           | 10        |
| 15602042242 | Black  | OD1 - 42,5 / OD2 - 42,5 | 52,0      | 52,0      | 36,5     | 145,5  | 11,200          | 10        |
| 15602054254 | Black  | OD1 - 54,5 / OD2 - 54,5 | 64,0      | 64,0      | 47,0     | 172,5  | 19,900          | 10        |

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.