


RQT

Connectors FLEXAquick for ROHRflex corrugated plastic tubings

Plastic T distributor, for rational tubing assembly by just putting on



Temperature: -40°C ... +120°C

Material: TPE plastics

IP class [acc. to EN 60529]: IP 66

APPLICATIONS:

- Application: machine and plant constructions / insulated electrical installations for application rules machine and plant constructions acc. to DIN EN 60204



FLEXA No.	Colour	OD [mm]	Ø B2 [mm]	Ø B1/3 [mm]	E [mm]	D [mm]	Ø F [mm]	C [mm]	Weight [kg/100]	PU [pcs.]
15020067203	Black	OD1/OD3 - 10,0 / OD2 - 10,0	17,5	17,5	32,5	46,5	4,0	18,3	0,500	10
15020067207	Black	OD1/OD3 - 13,0 / OD2 - 13,0	21,0	21,0	36,0	51,0	4,0	21,0	0,900	10
15020067208	Black	OD1/OD3 - 15,8 / OD2 - 15,8	25,0	25,0	44,0	63,0	4,0	24,5	1,500	10
15020067213	Black	OD1/OD3 - 28,5 / OD2 - 15,8	25,5	36,5	56,0	65,0	4,0	37,0	2,900	10
15020067205	Black	OD1/OD3 - 18,5 / OD2 - 18,5	26,5	26,5	48,5	70,5	4,0	24,3	1,700	10
15020067201	Black	OD1/OD3 - 21,2 / OD2 - 21,2	29,5	29,5	50,0	71,0	4,0	29,5	2,000	10
15020067209	Black	OD1/OD3 - 21,2 / OD2 - 28,5	36,5	32,0	51,0	78,0	4,0	29,5	2,700	10
15020067202	Black	OD1/OD3 - 28,5 / OD2 - 28,5	36,5	36,5	57,5	77,0	4,0	37,0	2,900	10
15020067211	Black	OD1/OD3 - 34,5 / OD2 - 34,5	42,5	42,5	64,0	85,0	4,0	42,0	4,200	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.