

RQW-F

Connectors FLEXAquick for ROHRflex corrugated plastic tubings


Plastic flange for all metric connectors with outer thread acc. to EN 60423, high density

Temperature:	-40°C +120°C				
Material:	PA plastics				

IP class [acc. to EN 60529]: IP 68

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen



APPLICATIONS:

- Application: machine and plant constructions / automation / electrical installations

FLEXA No.	Colour	OD [mm]	ØA [mm]	B [mm]	C [mm]	D [mm]	H [mm]	Ø [mm]	ØG [mm]	F [mm]	E [mm]	Weight [kg 100]	PU [pcs.]
15020077216	Black	21,2	20,0	46,0	42,0	36,0		5,5	29,5	36,0	70,0	2,100	10
15020077221	Black	28,5	27,0	65,5	61,0 D	53,0		6,6	37,0	45,0	85,5	4,200	10
15020077229	Black	34,5	33,0	67,0	U 77,0 M	54,0	U 36,0 U	6,6	44,0 U	50,0	110,0	6,500	10
15020077236	Black	42,5	38,0	85,0	84,5	73,0	30,0	6,6	52,0	64,5	104,0	7,800	10
15020077248	Black	54,5	50,0	86,0	100,0	73,0	30,0	6,6	64,0	76,0	121,0	8,900	10
15020077016	Grey	21,2	20,0	46,0	42,0	36,0		5,5	29,5	36,0	70,0	2,100	10
15020077021	Grey	28,5	27,0	65,5	61,0	53,0		6,6	37,0	45,0	85,5	4,200	10
15020077029	Grey	34,5	33,0	67,0	77,0	54,0	36,0	6,6	44,0	50,0	110,0	6,500	10
15020077036	Grey	42,5	38,0	85,0	84,5	73,0	30,0	6,6	52,0	64,5	104,0	7,800	10
15020077048	Grey	54,5	50,0	86,0	100,0	73,0	30,0	6,6	64,0	76,0	121,0	8,900	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.