


STK-P | PG thread

Accessories

Blind plug for PG threads



Temperature:	-30°C ... +100°C
---------------------	------------------

Material:	polyamide, fibre-glass reinforced
------------------	-----------------------------------

CHARACTERISTICS:

- Properties: resistant against light acids and soft lyes
- resistant against sea water, benzine and mineral oil



FLEXA No.	Thread type	Colour	C [mm]	Ø B [mm]	Weight [kg/100]	PU [pcs.]
10551000207	PG7	Black	6,0	15,0	0,120	100
10551000209	PG9	Black	6,0	19,0	0,150	100
10551000211	PG11	Black	6,0	22,0	0,210	100
10551000213	PG13, 5	Black	6,0	25,0	0,260	100
10551000216	PG16	Black	6,0	27,0	0,310	100
10551000221	PG21	Black	8,0	33,0	0,480	100
10551000229	PG29	Black	8,0	44,5	0,810	100
10551000236	PG36	Black	10,0	55,5	1,400	50
10551000007	PG7	Grey	6,0	15,0	0,120	100
10551000009	PG9	Grey	6,0	19,0	0,150	100
10551000011	PG11	Grey	6,0	22,0	0,210	100
10551000013	PG13, 5	Grey	6,0	25,0	0,260	100
10551000016	PG16	Grey	6,0	27,0	0,310	100
10551000021	PG21	Grey	8,0	33,0	0,480	100
10551000029	PG29	Grey	8,0	44,5	0,810	100
10551000036	PG36	Grey	10,0	55,5	1,400	50

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.