


ADM-MP | metric and PG thread

Accessories

Adaptor to combine different types of threads metric



Temperature: -40°C ... +200°C

Material: nickel-plated brass

CHARACTERISTICS:

- Properties: high stability
- incl. O-ring



FLEXA No.	Outer thread	Inner thread	L1 [mm]	L [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
10370M16P07	M16x1,5	PG7	5,0	8,0	17	0,530	100
10370M20P09	M20x1,5	PG9	6,0	9,0	22	1,090	100
10370M25P11	M25x1,5	PG11	7,0	10,0	27	1,900	100
10370M25P13	M25x1,5	PG13,5	7,0	10,0	27	1,500	100
10370M25P16	M25x1,5	PG16	7,0	18,0	27	2,500	100
10370M32P16	M32x1,5	PG16	8,0	11,0	34	3,810	50
10370M32P21	M32x1,5	PG21	8,0	11,0	34	1,820	50
10370M40P21	M40x1,5	PG21	8,0	12,0	43	7,080	25
10370M40P29	M40x1,5	PG29	8,0	12,0	43	2,830	25
10370M50P29	M50x1,5	PG29	9,0	13,0	55	11,300	10
10370M50P36	M50x1,5	PG36	9,0	13,0	55	3,900	10
10370M63P36	M63x1,5	PG36	10,0	14,0	65	18,740	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.