## EEK

### Connectors

Terminal sleeve | ferrule for connectors USK as terminal sleeve for protective conduits AIRflex




| | |
|---|---|
| **Temperature:** | -10°C ... +110°C |
| **Material:** | plastics |

**APPLICATIONS:**

- Application: for connectors USK / as terminal sleeve for protective conduits AIRflex®

| FLEXA No. | OD [mm] | Conduitmaß [mm] | Ø l [mm] | Weight [kg/100] | PU [pcs.] |
|---|---|---|---|---|---|
| **15020030007** | 10,0 | 7,0-10,0 | 6,0 | 0,040 | 50 |
| **15020030009** | 14,0 | 10,0-14,0 | 9,0 | 0,060 | 50 |
| **15020030011** | 17,0 | 13,0-17,0 | 11,5 | 0,100 | 50 |
| **15020030013** | 19,0 | 15,0-19,0 | 13,0 | 0,120 | 50 |
| **15020030016** | 21,0 | 16,0-21,0 | 14,5 | 0,140 | 50 |
| **15020030021** | 27,0 | 21,0-27,0 | 19,5 | 0,200 | 25 |
| **15020030029** | 36,0 | 29,0-36,0 | 26,5 | 0,400 | 25 |
| **15020030036** | 45,0 | 38,0-45,0 | 36,0 | 0,600 | 20 |
| **15020030048** | 56,0 | 48,0-56,0 | 45,5 | 0,770 | 10 |

IBS ELECTRO PRODUCTS CORP.

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA´s knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.