


EEM

Connectors

Terminal sleeve | ferrule for connectors US and USW, as terminal sleeve for protective conduits



Temperature: -40°C ... +250°C

Material: brass

for protective conduit: SPR-PA / SPR-PU-F /
SPR-PVC-AS /
SPR-PU-AS /
SPR-EDU-AS /
SR-CU-AS

APPLICATIONS:

- Application: for connectors US and USW / as terminal sleeve for protective conduits



FLEXA No.	OD [mm]	Conduitmaß [mm]	Ø l [mm]	Weight [kg/100]	PU [pcs.]
15031028007	10,0	7,0-10,0	6,0	0,160	50
15031028009	14,0	10,0-14,0	8,5	0,300	50
15031028011	17,0	13,0-17,0	11,5	0,320	50
15031028013	19,0	15,0-19,0	13,5	0,420	50
15031028016	21,0	17,0-21,0	15,5	0,520	50
15031028021	27,0	22,0-27,0	20,5	1,120	25
15031028029	36,0	29,0-36,0	27,5	1,640	25
15031028036	45,0	38,0-45,0	36,5	2,450	20
15031028048	56,0	49,0-56,0	47,5	3,800	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.