


LI-P | PG thread

Connectors

Metal connector, straight, turnable, PG outer thread, integrated ferrule [brass]

Temperature:	-40°C ... +250°C
Material:	nickel-plated brass
IP class [acc. to EN 60529]:	IP 40
for protective conduit:	SPR-AS / SPR-VA / SPR,-PVC / SPR-PA / SPR-PU-AS / SPR-PU-F / FLEXAgraff-AS / FLEXAgraff-VA / FLEXAgraff-PU-AS



APPLICATIONS:

- Application: machine and plant constructions / automotive / shipbuilding / automation / electrical installations

CHARACTERISTICS:

- Properties: integrated conduit screw out
- covering of the conduit ends
- vibrationproof and tensionproof




ELECTRO-PRODUCTS CORP.

FLEXA No.	OD [mm]	Thread type	Conduit ID	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15010010007	10,0	PG7	7,0	10,0	6,0	16,0	7,0	29,0	15	1,580	50
15010010009	14,0	PG9	10,0	14,0	9,0	21,0	7,0	30,0	19	2,240	50
15010010011	17,0	PG11	13,0	17,0	12,0	24,5	7,0	30,0	23	2,920	50
15010010013	19,0	PG13,5	15,0	19,0	13,5	27,0	7,0	30,0	25	3,560	50
15010010016	21,0	PG16	17,0	21,0	15,5	29,0	7,0	32,0	27	4,040	50
15010010021	27,0	PG21	22,0	27,0	20,5	37,0	10,0	35,0	34	6,760	25
15010010029	36,0	PG29	29,0	36,0	27,5	46,0	10,0	40,0	43	11,000	25
15010010036	45,0	PG36	38,0	45,0	36,5	58,0	10,0	40,0	55	13,500	25
15010010048	56,0	PG48	49,0	56,0	47,0	68,0	10,0	40,0	66	19,500	10
15010710007	10,0	PG7	7,0	10,0	6,0	16,0	7,0	29,0	15	1,580	10
15010710009	14,0	PG9	10,0	14,0	9,0	21,0	7,0	30,0	19	2,240	10
15010710011	17,0	PG11	13,0	17,0	12,0	25,0	7,0	30,0	23	2,920	10
15010710013	19,0	PG13,5	15,0	19,0	13,5	27,0	7,0	30,0	25	3,560	10
15010710016	21,0	PG16	17,0	21,0	15,5	29,0	7,0	32,0	27	4,040	10
15010710021	27,0	PG21	22,0	27,0	20,5	37,0	10,0	35,0	34	6,760	10
15010710029	36,0	PG29	29,0	36,0	27,5	46,0	10,0	40,0	43	11,000	2
15010710036	45,0	PG36	38,0	45,0	36,5	58,0	10,0	40,0	55	13,500	2
15010710048	56,0	PG48	49,0	56,0	47,0	68,0	10,0	40,0	66	19,500	2

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.