


**RQBK45DR-M****Connectors FLEXAquick for ROHRflex corrugated plastic tubings**

Plastic connector, quick-type, bend 45°, turnable, metric outer thread, high-density, incl. O-ring (OR) and flat sealing (FRH), EN 45545-2 (HL3)



**Temperature:** -40°C ... +120°C

**Material:** PA plastics | nickel-plated brass 58


**IP class [acc. to EN 60529]:** IP 68 | IP 69K

**CHARACTERISTICS:**

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium and halogen

**APPLICATIONS:**

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations

FLEXA No.	Colour	OD [mm]	Thread type	Ø I [mm]	Ø B [mm]	C [mm]	E [mm]	F [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15131021220	Black	21,2	M20 x 1,5	13,0	29,5	12,0	54,5	71,5	27	6,200	50
15131421220	Black	21,2	M20 x 1,5	13,0	29,5	6,0	54,5	65,5	27	5,740	50
15131028225	Black	28,5	M25 x 1,5	17,0	37,0	13,0	66,0	87,0	34	11,060	25
15131428225	Black	28,5	M25 x 1,5	17,0	37,0	7,0	66,0	81,0	34	10,350	25
15131034232	Black	34,5	M32 x 1,5	24,5	44,0	14,0	74,0	92,0	43	16,500	10
15131434232	Black	34,5	M32 x 1,5	24,5	44,0	8,0	74,0	86,0	43	15,500	10
15131042240	Black	42,5	M40 x 1,5	31,5	52,0	17,0	85,0	104,0	52	28,400	50
15131442240	Black	42,5	M40 x 1,5	31,5	52,0	8,0	85,0	95,0	52	26,300	50

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.