

RQG-M | metric thread

Protective conduit systems | UL listed

Plastic connector, quick-type, straight, metric outer thread, integrated snap-in sleeve with sealing, high density



Temperature: -40°C ... +120°C

Material: PA plastics

IP class [acc. to EN 60529]: IP 68 | IP 69K

CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen

APPLICATIONS:

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations



FLEXA No.	OD [mm]	Colour	Thread type	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020037220	21,2	Black	M20 x 1,5	15,0	29,5	13,0	44,5	27	1,120	50
15020065209	21,2	Black	M25 x 1,5	17,0	29,5	13,0	44,5	27	1,240	50
15020037225	28,5	Black	M25 x 1,5	19,5	37,0	13,0	47,0	34	1,680	25
15020065211	28,5	Black	M32 x 1,5	23,5	37,0	15,0	49,0	34	1,800	25
15020037232	34,5	Black	M32 x 1,5	25,5	44,0	15,0	51,0	40	2,400	25
15020037238	34,5	Black	M40 x 1,5	30,5	48,5	15,0	44,5	40	2,560	25
15020037240	42,5	Black	M40 x 1,5	32,0	58,0	17,0	76,0	55	5,800	25
15020037245	42,5	Black	M50 x 1,5	37,5	63,0	17,0	76,0	60	6,720	25
15020037250	54,5	Black	M50 x 1,5	42,5	68,0	17,0	88,0	65	8,300	10
15020037263	54,5	Black	M63 x 1,5	49,0	74,0	17,0	88,0	70	10,150	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.