

## RQG-N | NPT thread

## Protective conduit systems | UL listed

Plastic connector, quick-type, straight, NPT outer thread, integrated snap-in sleeve with sealing, high density



**Temperature:** -40°C ... +120°C

**Material:** PA plastics

**IP class [acc. to EN 60529]:** IP 68 | IP 69K

## CHARACTERISTICS:

- Properties: resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen

## APPLICATIONS:

- Application: machine and plant constructions / automotive / railway industry / shipbuilding / automation / electrical installations



FLEXA No.	Colour	OD [mm]	Thread type	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020056206	Black	21,2	OD 21,2, NPT 1/2 inch	15,5	29,5	13,0	44,0	27	1,140	50
15020038221	Black	28,5	OD 28,5, NPT 3/4 inch	20,7	37,0	14,0	47,5	34	1,680	25
15020038227	Black	34,5	OD 34,5, NPT 1 inch	25,7	44,0	16,0	52,0	40	2,200	25
15020056207	Black	42,5	OD 42,5, NPT 1 1/4 inch	34,0	52,0	18,0	47,5	40	1,520	25
15020056208	Black	42,5	OD 42,5, NPT 1 1/2 inch	36,5	55,0	18,0	55,5	49	3,500	25
15020056209	Black	54,5	OD 54,5, NPT 1 1/2 inch	39,5	64,0	18,0	57,0	60	4,400	10
15020056210	Black	54,5	OD 54,5, NPT 2 inch	48,5	64,0	21,0	60,0	60	4,500	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.