RQMR

Tubing clamp systems for light, medium and heavy duty applications, EN 45545-2 (HL3)

Reducer for tubing clamp RQM with ribbed fixing for strain relief, EN 45545-2 (HL3)



Temperature:	-40°C ...+120°C
Material:	PA plastics

CHARACTERISTICS:

- Properties: ribbed fixing for strain relief

APPLICATIONS:

- Application: for heavy duty applications / machine and plant constructions / insulated electrical installations for application rules machine and plant constructions acc. to DIN EN 60204 / Railway Industrie

FLEXA No.	Colour	OD holder [mm]	OD [mm]	Weight [kg/100]	PU [pcs.]
15605028213	Black	28,5	13,0	1,000	10
15605028215	Black	28,5	15,8	1,000	10
15605028221	Black	28,5	21,2	1,000	10
15605042215	Black	42,5	15,8	2,100	10
15605042221	Black	42,5	21,2	1,800	10
15605042228	Black	42,5	28,5	1,600	10
15605042234	Black	42,5	34,5	1,100	10
15605054228	Black	54,5	28,5	3,500	10
15605054234	Black	54,5	34,5	3,000	10
15605054242	Black	54,5	42,5	2,300	10

IBS ELECTRO-PRODUCTS CORP.

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA´s knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.